



% OF RATING	OPENING TIME	
	MINIMUM	MAXIMUM
100	100 HRS	-
135	120 S	1800 S
200	10 S	300 S
350	1 S	15 S
600	0.3 S	5 S

NOTES:
 INTERRUPT RATING: 2000A @ 32VDC
 VOLTAGE RATING: 32VDC
 TEMP. RATING: -40°C - 125°C
 CABLE TYPE: XLPE INSULATED, SAE J1128 GXL (8AWG) COLOR RED.
 SPECIFICATION: MEETS LITTELFUSE'S VS-006013 SPECIFICATION
 APPLICATION: DESIGNED FOR UNDERHOOD INSTALLMENT.
 BAR CODE OR DATE CODE: THE BAR CODE OR DATE CODE IS USED FOR LOT TRACEABILITY. IT IS LOCATED ON ONE OF THE CABLE LEADS.

METRIC
ASSEMBLY

●	CRITICAL CHARACTERISTIC FOR PART FUNCTION.
CPK	CPK DIMENSION. 1.33 MINIMUM CPK VALUE ON NEW TOOLING.
ST	STATISTICAL PROCESS CONTROL DIMENSION. THIS DIMENSION INDICATES PROCESS PERFORMANCE. DATA SHALL BE TRACKED AND ANALYZED AT PERIODIC TIMES, ACC. TO CONTROL PLAN.
CP	CP DIMENSION. 1.33 MINIMUM CP VALUE. MUST BE INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.
△	CLAMP DIMENSION. PARTS SHALL BE SECURED BEFORE TAKING DIMENSIONAL MEASUREMENTS. FIXTURING DATUMS & PROCEDURES TO BE DEFINED IN NOTES OR SEPARATE PROCESS DOCUMENTS.

DIMENSIONS & TOLERANCES ACC. TO ASME Y14.5-2009	MATERIAL SPEC	FINISH	SCALE 1:1	DRW	OPL	CHK	SLD	DATE	05/SEP/16	
				DRW	OPL	CHK	SLD	DATE	05/SEP/16	
TOLERANCES UNLESS OTHERWISE SPECIFIED										
LINEAR DIMENSIONS										
DIM	UP TO .5	UP TO .6	UP TO 6	UP TO 30	UP TO 120	UP TO 400	RADIO			
TOL	±0.1	±0.2	±0.3	±0.5	±0.5	±0.5	ANGLES			
TITLE							CABLEPRO 32V 80A 850MM + 53MM			
LITTELFUSE CHICAGO, USA 773-628-1000										
REVISION DRWG. NO. A OL-0496080-ZXL										
LTR	DATE	REVISION						DRW		
A	05/SEP/16	51631 IGCA-RELEASED						OPL		