



| % OF RATING | OPENING TIME | |
|-------------|--------------|---------|
| | MINIMUM | MAXIMUM |
| 100 | 100 HRS. | - |
| 135 | 120 S | 1800 S |
| 200 | 10 S | 300 S |
| 350 | 1 S | 15 S |
| 600 | 0.3 S | 5 S |

NOTES:

- INTERRUPT RATING: 2000A @ 32VDC
- VOLTAGE RATING: 32VDC
- TEMP. RATING: -40°C - 125°C
- CABLE TYPE: XLPE, SAE J1127, STX (4AWG)
- SPECIFICATION: MEETS LITTELFUSE'S VS-006013 SPECIFICATION
- APPLICATION: DESIGNED FOR UNDERHOOD INSTALLMENT.
- BAR CODE OR DATE CODE: THE BAR CODE OR DATE CODE IS USED FOR LOT TRACEABILITY. IT IS ON ONE OF THE CABLE LEADS.

| NO | | COMPONENT NO | DESCRIPTION | QTY/M | U/M |
|-------------------------|----|------------------------|-------------|-------|--|
| BILL OF MATERIAL | | | | | |
| COPIES TO | | MATERIAL SPEC | | | |
| 1 | 9 | 18 | DRW | DATE | 11/10/06 |
| 2 | 10 | 19 | DHM | SCALE | FULL |
| 3 | 12 | 20 | CHK | DATE | SUPER DRW |
| 4 | 13 | 21 | APPD | DATE | FINISH GOOD WT |
| 5 | 14 | 23 | | DATE | GRAMS/PIECE |
| 6 | 15 | 33 | | | |
| 7 | 16 | 43 | | | TOLERANCE UNLESS OTHERWISE SPECIFIED |
| 8 | 17 | 53 | | | TWO PLACE DEC ±.25[.01] FRACTION ± THREE PLACE DEC ±.100[.004] ANGULAR ±1° |
| TRIPLE ANGLE PROJECTION | | TITLE | | | |
| | | CABLEPRO | | | |
| | | DRWG. NO. 0496200.ZXAH | | | |
| | | REVISION B | | | |
| | | OUTLINE | | | |

| LTR | REVISION | CHK | APD |
|-----|--|-----|-----|
| A | 63080 - RELEASED 11/10/06 DHM | | |
| B | 85286D-CHG LEAD 2 STRIP LGTH FROM 20±1. 01/12/07 DHM | | |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN BRACKETS [] ARE INCHES. UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING. DENOTES CRITICAL CHARACTERISTICS. DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC IS FOUND IN THE LITTELFUSE INSTRUCTION BOOKS. CP DIMENSIONS, -MINIMUM CP VALUE DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC IS FOUND IN THE LITTELFUSE INSTRUCTION BOOKS. DIMENSIONS WITHIN THE DIMENSIONAL LIMITATIONS AND TOLERANCES ARE TO BE WITHIN THE DIMENSIONAL LIMITATIONS AND TOLERANCES SPECIFIED IN THE DRAWING AND INITIALLY LOCATED TO THE DIMENSION LINE OR MAXIMUM TOOL LIFE.

UNCONTROLLED DOCUMENT

