

	REVISION						
REV	DATE	DESCRIPTION					
Α	8/9/22	525548GCP - RELEASE MRY					





APPROXIMATE SHIPPING WEIGHT: 10 FUSES / 0.17 LBS.

1	COMPONENT NO				OTV/M	11/04			
NO COMPONE		N I NO	DESCRIPTION BILL OF MATERIAL			QTY/M	U/M		
S> CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE									
		DENOTES CRITICAL CHARACTERISTICS.							
<u> </u>									
	CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE							
<	<u>st</u> >	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.							
CP DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.							A		
MATL :	SPEC			FINISH	FINISH				
DRW JMoler			DATE 8/8/2022	SCALE NTS		FINISH GOOD WT  GRAMS/PIECE			
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [ ] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994									
	3RD ANGLE PROJECTION								
TITLE 592 1/10-30A OUTLINE									
	/4 1 i+	telfuse®		REVISION	DRWG NO.	SHEE	Γ 1 OF 1		
CHICAGO, ILLINOIS 60631				Α	OL-0592	2030			