


MM	IN
6.35	.250
9.14	.360
11.17	.440
36.57	1.440
51.05	2.010




FACE NUT

5/8-32 UN THD
- L'WASHER


DATE CODE ETCHED ON
-SIDE OF CASE AT RANDOM
LOCATION

-SCREW, 8-32 x 6.35 LG



36.57
REF

OPTIONAL KEY



USED WITH
"B" TYPE SWITCH

METRIC

NOTES:

1. APPLICABLE SAE STANDARD OR RECOMMENDED PRACTICE SAE J259
2. "A" TYPE SWITCH SHOWN.
3. "O" RING SEAL AT BUSHING.
4. ALL STEEL PARTS PLATED.

Confidential Property of Cole Hersee

95525B	83353 2 KEYS RINGED
95525A	83357 2 KEYS RINGED
95525 BASIC	— H —
SWITCH NO.	KEY PART NO.

DO NOT SCALE

LET.	WAS	DATE	BY	LET	WAS	DATE	BY	MATERIAL #	DRAWN SB	CHECKED <i>[Signature]</i>	APPRO'D. 	SCALE 1:1		DATE DRAWN 12-26-62
								FINISH #						DATE BLUEPRINT
			K	J	01535 REDRAWN	9/10/61 7-16-64	PH CB	TOLERANCES DECIMAL ± METRIC ±	C.H. Cole Hersee Co. 800 E. COLONY AVENUE, SOUTH WESTON, ILL., U.S.A. 60177 SWITCH, IGNITION & START, 4 POS.					95525