



ITEM NO.	PART NUMBER	DESCRIPTION	Default/ QTY.
1	890011640	3 Position Base	1
2	908-082	M10 Insulated Stud	3
3	901-730	Cover, 3 Position BMZS	1

DIMENSIONS ARE SHOWN IN MILLIMETERS. DIMENSIONS AND TOLERANCES ARE DEFINED ACCORDING TO ANSI/ASME Y14.5-1994.			
PER CHNPD20-008 PROCEDURE	●	FIT/ FUNCTION CRITICAL CHARACTERISTICS	
	<S>	SAFETY/ COMPLIANCE CRITICAL CHARACTERISTICS SYMBOL	
	CPK	DENOTES CPK DIMENSIONS MINIMUM CPK VALUE	
	(ST)	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE.PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS	
	CP	DENOTES CP DIMENSIONS. -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE	
DRAWN		NAME	DATE
CHECKED		B.CARR	7/8/2021
		S.CASTILLO	10/15/2021
FORM NO. CVP-PE40-0005 REV B			
THIRD ANGLE PROJECTION			
DO NOT SCALE DRAWING		SCALE 1:25:1	SHEET 1 OF 1

Littelfuse	
Expertise Applied   Answers Delivered	
TITLE	
BMZS STUDDED 3 POS KIT BULK	
SIZE	REV.
C	B
DWG. NO.	
OUTLINE	
OL-FHZ00863	