



1						
NO	COMPONENT NO		DESCRIPTION		QTY/M	U/M
BILL OF MATERIAL						
<s></s>		CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE				
•		DENOTES CRITICAL CHARACTERISTICS.				
CPK		DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE				
<u>(ST)</u>		DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.				
СР		DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.				
MATL SPEC				FINISH		
DRW JMoler		-	DATE 5/20/2023	SCALE NTS	FINISH GOOD V	WT 1S/PIECE
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN						

BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

L25S 70-200A OUTLINE

REVISION

Α

DRWG NO.

OL-L25S200

SHEET 1 OF 1

3RD ANGLE PROJECTION

TITLE

 22.7 ± 0.25

 $[0.895 \pm 0.010]$