

Model 239*+ followed by 0.08 thru 3.5.

File Number: E10480

COMPANY

LITTELFUSE INC
6133 N. River Rd, Suite 500
Rosemont, IL 60018 United States

MODEL INFO

239*+ followed by 0.08 thru 3.5.
Supplemental fuses: time delay, cartridge enclosed

SUPPLEMENTAL FUSES	VALUE
Micro Fuse	No
Pigtail Leads	No
Surface Mount	No
Cartridge Enclosed	Yes
Time Delay	Yes
Paper Tube	No
Filled Tube	No
OD - Length	5 mm
Length - Width	20 mm

RATING TABLE				
Amps Minimum (A)	Amps Maximum (A)	Voltage (V)	Voltage Source	Interrupting Rating (A)
0.08	1	250	ac	35
1.25	3.5	250	ac	100
0.08	3.5	125	ac	10000

Report Date: 1985-05-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

